

NZ4326

Glittering window film

Description:

Film: 80micron gray glittering PVC film
Glue: Permanent transparent glue
Liner: 120gsm silicon paper with one side PEK coating
Width: 0.914/1.27/1.37/1.52m

Features:

1. Shading, protection of personal privacy.
2. Good dimensional stability and is suitable for most media surfaces;

Applications:

It is suitable for glass applications, as well as transparent acrylic board, PVC, PET transparent board, etc.

Technical Data:

Testing condition: Indoor temperature 23±2°C, Relative humidity 50±5%

Test Items	Units	Test method	Average value
Thickness PVC	Micron	GB/T6672-2001	80±10
Weight-Liner	g/m ²	GB4669-1995	120±10
Weight -finished product	g/m ²	GB4669-1995	250±20
Gloss Rate 60°	%	GB8807-88	≥60
Initial Adhesion	N/25mm	FTM 9	≥5
24h, 180°peel	N/25mm	FTM 1	≥9
Dimensional stability MD	mm	FTM 14	≤1.2
Dimensional stability CD	mm	FTM 14	≤1.0
Tensile strength MD	N/25 mm	GB/T1040.1-2006	≥45
Tensile strength CD	N/25 mm	GB/T1040.1-2006	≥35
Construction Temperature	°C		20±10°C
Applicable Temperature	°C		-20 ~ +70

Storage Condition:

All NAR products need to be stored in the original packing and with the original protection materials, preferably stored hermetically and vertically, do not expose to direct sunlight or heat sources. In order to avoid loss of quality, NAR products should also be stored in suitable conditions, that is at a temperature of 25°C ± 5°C and a relative humidity of 50 ± 15%. Under these conditions, NAR products can be stored up to one year.

Production and Application Environment:

Production environment: temperature of 25 ± 5 °C, relative humidity of $50\% \pm 10\%$, clean dust-free environment without suspended matter; Please move the materials to the printing environment 24 hours before printing. Printing test before use. Due to the different matching equipment, the ink should be tested before use. It is suggested that enough blank margin should be left while printing .

Pasting requirements: 20 ± 10 °C, relative humidity $50 \pm 10\%$; pasted on the flat, smooth, clean surface without dust, the maintenance time needs more than 2 hours.

Warranty Condition :

1. One year service life: stored in suitable conditions, preferably use within 6 months.
2. One year prosecution period: from the product manufacture date, no-acceptance for overdue product.

Important Remark:

The information mentioned in this product data sheet is based upon tests that were executed by NAR, and that we consider to be reliable. This product is a with permanent glue, there will be risk of residue to paste on different substrate and pasting time, so splicing is not recommended for different batches of products.

NAR
IDEAS FOR SIGN